

Especificaciones del producto

P554403

FILTRO DE LUBRICANTE, FLUJO PLENO ENROSCABLE

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.



Atributos

Diámetro exterior	93 MM (3.66 Pulgadas)
Tamaño de la rosca	3/4-16
Longitud	136 MM (5.35 Pulgadas)
Diámetro externo de empaque	71 MM (2.80 Pulgadas)
Diámetro interno de empaque	61 MM (2.40 Pulgadas)
Eficiencia 99%	40 MICRÓN
Prueba de eficiencia estándar	SAE J806

Válvula antidrenaje	Sí
Válvula de desvío	Sí
Ajuste de la válvula de derivación LR	0.5 Bar (7 PSI)
Ajuste de la válvula de derivación HR	0.7 Bar (10 PSI)
Tipo de medio	Cellulose
Ráfaga de colapso	6.9 Bar (100 PSI)
Tipo	Full-Flow
Estilo	Spin-On
Aplicación principal	PERKINS 2654403

Otra información

Código UPC	742330044674
------------	--------------

La información contenida en el presente es de naturaleza general y tal vez no refleje la información real sobre la pieza al momento del envío. Las piezas pueden provenir de más de un país; el país de origen real y el Código HS se indicarán en las Facturas comerciales adjuntas a los productos.