



Especificaciones del producto

P550367

FILTRO DE LUBRICANTE, FLUJO PLENO ENROSCABLE

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.



Atributos

Diámetro exterior	136 MM (5.35 Pulgadas)
Tamaño de la rosca	M36 x 1.5
Longitud	308 MM (12.13 Pulgadas)
Diámetro externo de empaque	110 MM (4.33 Pulgadas)
Diámetro interno de empaque	100 MM (3.94 Pulgadas)
Eficiencia 99%	21 MICRÓN
Prueba de eficiencia estándar	SAE J1858

Válvula de desvío	Sí
Ajuste de la válvula de derivación LR	1.8 Bar (26 PSI)
Ajuste de la válvula de derivación HR	2.1 Bar (30 PSI)
Tipo de medio	Cellulose
Ráfaga de colapso	10.3 Bar (149 PSI)
Tipo	Full-Flow
Estilo	Spin-On
Aplicación principal	NAVISTAR 1819452C1

Otra información

Código UPC	742330042342
------------	--------------

La información contenida en el presente es de naturaleza general y tal vez no refleje la información real sobre la pieza al momento del envío. Las piezas pueden provenir de más de un país; el país de origen real y el Código HS se indicarán en las Facturas comerciales adjuntas a los productos.