

Especificaciones del producto

P553771

FILTRO DE LUBRICANTE, FLUJO PLENO ENROSCABLE

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.



Atributos

Diámetro exterior	93 MM (3.66 Pulgadas)
Tamaño de la rosca	1-12 UN
Longitud	200 MM (7.87 Pulgadas)
Diámetro externo de empaque	71 MM (2.80 Pulgadas)
Diámetro interno de empaque	61 MM (2.40 Pulgadas)
Eficiencia 99%	40 MICRÓN
Prueba de eficiencia estándar	ISO 4548-12

Válvula antidrenaje	Sí
Válvula de desvío	Sí
Ajuste de la válvula de derivación LR	2 Bar (29 PSI)
Ajuste de la válvula de derivación HR	2.5 Bar (36 PSI)
Tipo de medio	Cellulose
Ráfaga de colapso	6.9 Bar (100 PSI)
Tipo	Full-Flow
Estilo	Spin-On

Otra información

Código UPC	742330044445
------------	--------------

La información contenida en el presente es de naturaleza general y tal vez no refleje la información real sobre la pieza al momento del envío. Las piezas pueden provenir de más de un país; el país de origen real y el Código HS se indicarán en las Facturas comerciales adjuntas a los productos.